

Pressed Steel Basket

Ferrite Magnet

Paper Diaphragm


080

17


SDS-135F25CP02-04

NBR Rubber Surround





SPECIFICATIONS			
Transducer Size		5.25	in
Impedance		4	Ω
Frequency Range ¹		50 - 1000	Hz
Sensitivity ² (2.83V 1W @ 1m)		87 84	dB
Power Rating (IEC 268-5)		50	W
Voice Coil Size		25.7	mm
Air Gap Winding Height	H _{ag} H _{vc}	6 16.4	mm
Net Weight		0.96	kg
PARAMETERS ³			
Eff. Piston Area	s _d	86.6	cm ²
DC Resistance	R _e	3.1	Ω
Minimum Impedance	Z _{min}	4	Ω
Inductance	L _e	1.06	mH
Resonance Frequency ⁴	Fs	58	Hz
Mechanical Q Factor	Q _{ms}	3.68	-
Electrical Q Factor	Q _{es}	0.447	-
Total Q Factor	Q _{ts}	0.4	-
Moving Mass	M _{ms}	20.4	g
Compliance	C _{ms}	370	μm/N
Equivalent Volume	V _{as}	3.94	L
Motor Force Factor	BI	7.2	Tm
Motor Efficiency	β	16.6	(BI) ² / R _e
Linear Excursion ⁵	X _{max}	7.2	mm
Max Mechanical Excursion ⁶	Xmech	-	mm



Details on this spec sheet are for reference only and should not be used for setting production limits. Specifications and product cosmetics are subject to change without notice. Peerless is a registered trademark of Tymphany Enterprises. All measurements conducted in test lab at 25°C ±10°C, 50%RH ±10%. ¹ Specified by Engineering as linear working range of transducer. ² Measured at 2.83V at 1m and normalized to 1W with respect to nominal impedance. ³ Measured in Free Air without preconditioning, therefore subject to some deviation. ⁴ Impedance and Fs value measured under different conditions. ⁵ Equal/Overhung: $(H_{vc} - H_{ag})/2 + H_{ag}/3$. Underhung: $(H_{ag} - H_{vc})/2 + H_{vc}/3$. ⁶ Mechanically limited excursion (e.g. bottoming, spider crash).